



The Ox Gravity Wagon Augers come with a hydraulic motor, control valve with remote rope control, and spring-loaded shut-off. Its universal mount fits many wagons and seed transports, and you can choose between cupped plastic or bristle flighting. Build it however you'd like. Just don't keep Ox waiting.

# **GRAVITY WAGON AUGER**

## STANDARD FEATURES

- Universal hopper fits most wagons and seed transports.
- Easy installation and removal.
- Simple operation: pull the rope to start the auger and release to stop.
- Auger swings left to right and raises or lowers.

## **SPECIFICATIONS**

| Auger Lengths   | 6" augers available in 12, 14 and 18 ft. lengths.  |  |
|-----------------|--|--|
|                 | 8" auger available in 12 ft. length.   |  |
| Auger Tube      | 14 ga. cold drawn welded tube.   |  |
| Flighting       | High density polyethylene cupped plastic modules on hex tube; nylon bristle flight with steel center.            |  |
| Auger Drive     | Char Lynn 6.2 CID "H" Series hydraulic motor, control valve with remote rope control and spring-loaded shut-off. |  |
| Transfer Hopper | Universal mount fits many gravity wagons and seed transports; designed for easy installation and removal.        |  |

#### **FLIGHTING TYPES**

- Cupped plastic flighting plastic flights work great for conveying fertilizer and seed gently.
- Bristle flight high capacities with drastic reductions in seed damage.



UNIVERSAL HOPPER

### WAGON AUGER CAPACITIES

| E de la constante de la consta | 6"      | 8"        |
|--|---------|-----------|
| Plastic Flight   | 875 BPH | 1,600 BPH |
| Bristle Flight   | 500 BPH | 1,360 BPH |

#### **OPTIONAL FEATURES**

- Solenoid valve control Remote auger operation. Eliminates constant rope tension required for auger operation.
- Hydraulic Power kit 8 HP gas engine. 9 GPM hydraulic pump. Manual or electric start.
- 4' urethane spout
- Three-piece telescoping spout (to 15½')



CUPPED PLASTIC FLIGHTING



STEEL CORE BRISTLE FLIGHT



THERE'S WORK TO DO.