

GRAIN > DRAG CHAIN CONVEYORS >
LOW-PROFILE CONVEYORS

Sudenga's innovative low-profile conveyors feature up to 17,500 bushels per hour capacity with the advantage of minimized installation cost and the long-term durability of drag conveyors. Great in retrofit commercial applications where space or ground water is an issue.

Sudenga®
INDUSTRIES, INC.



WWW.SUDENGA.COM

- Eliminate water problems common in pit installations. The 16" (2610), 19" (4012), or 26" (4019) deep trench is open at both ends for drainage.
- Unloading rates from 3000 to 17,500 BPH.
 - Modular design for variable lengths and discharge heights.
- Cover and grate sections for the "drive over" area are available in various lengths to accommodate various width trenches.



Learn more
or get a quote



1-888-SUDENGA | 1-712-475-3301 | Fax: 1-712-475-3320
PO Box 8, 2002 Kingbird Ave., George, IA 51237 USA
sales@sudenga.com | www.sudenga.com

**MADE
★ IN THE ★
USA**

LOW-PROFILE CONVEYORS

MODEL 2610

UP TO 7000 BPH

- 3000, 5000 and 7000 BPH unloading rates
- 10 ga. galv. trunking housing
- 22.5°, 45° & 60° elbow and head sections
- 12" x 12" discharge reducer
- Single or double 81X chain configurations with polyethylene paddles
- 11.5" deck height
- Modular sections available in 1', 2', 5' and 10' lengths.
- Conveyors require a trough 32" wide and 16" deep. Trench can be left open at ends for drainage.



Model 2610

MODEL 4012

UP TO 10,000 BPH

- 5000, 7000 and 10,000 BPH unloading rates
- 10 ga. galv. trunking housing
- 22.5°, 45° & 60° elbow and head sections
- Discharge opening 21" x 40" or 12" x 24" reducer
- Double 81X chain with polyethylene paddles
- 14" deck height
- Modular sections available in 1', 2', 5' and 10' lengths.
- Conveyors require a trough 48" wide and 19" deep. Trench can be left open at ends for drainage.



Model 4012

MODEL 4019

UP TO 17,500 BPH

- 12,500, 15,000 and 17,500 BPH unloading rates
- 10 ga. galv. trunking housing with 7 ga. dividers
- 22.5° & 45° elbow and head sections
- 14" x 14" and 16" x 16" discharge reducer
- Double 81XHH chain with polyethylene paddles
- Outboard mounted pillow block bearings with dust seals
- 21" deck height
- Modular sections available in 1', 2', 3', 5' and 10' lengths.
- Conveyors require a trough 48" wide and 26" deep. Trench can be left open at ends for drainage.




Model 2610

Model 4012

ALL LOW-PROFILE CONVEYORS ALSO FEATURE:

- Combination heavy gauge galvanized and painted trunking sections.
- Painted head, curves and tail sections. (Standard paint color is blue)
- Commercial duty shaft mount gear reducer
- Heavy duty head and tail sprockets on turned ground and polished shafts
- Head mounted inspection/overflow panel
- Intake grates and solid drive over covers can be repositioned for full width, center or side discharge situations. Grates and bridges available in 24" x 32", 12" x 48", 24" x 48".
- Gated grates and flow restrictor pans available



**MADE
★ IN THE ★
USA**

*Learn more
or get a quote*



1-888-SUDENGA | 1-712-475-3301 | Fax: 1-712-475-3320
PO Box 8, 2002 Kingbird Ave., George, IA 51237 USA
sales@sudenga.com | www.sudenga.com